

February 2006 Newsletter

Volume 6, Number 1

In This Issue

- BC Biomedical's New Defibrillator Analyzer
- BC Biomedical's NIBP Simulator
- BC Depot Calibration Capabilities
- BC Biomedical's Infusion Pump Testers

Category of Links

<u>Home</u>

2005 Catalog (4MB)

Company

News

Process Control

Online Store

Contact Us

www.bcgroupintl.com sales@bcgroupintl.com



BC Biomedical's New Defibrillator Analyzer

Introducing the BC Biomedical DA-2006 (left) & DA-2006P (right). The DA-2006 is a microprocessor -based instrument series that is used in the testing of defibrillators. It measures



the energy output & provides information about the pulse. It is used on manual, semi-automatic & automatic defibrillators with monophasic or biphasic outputs. The DA-2006P measures and displays pacer pulse information as well as performing Refractory Period, Sensitivity & Immunity testing.

- ♦ Backlit display screen ♦ Waveform storage & playback
 - Unique protection for the Pacing Board

BC Biomedical's NIBP Simulator



The BC Biomedical NIBP-1000 series; a new family of high quality, low cost, high function micro-processor based NIBP Simulators. They were designed to meet the demand for a small, easy to use unit with multiple features to fit your exact needs.

- ♦ Multiple display screens ♦ ECG waveforms
- ±1% of reading pressure accuracy
- Adult, Neonatal & Hypertensive modes
 - ♦ SpO₂ Ready ♦ RS232 Interface

BC Depot Calibration Capabilities

Our Depot Calibration capabilities are ever expanding. Added are the TSI Certifier Ventilator Tester & the Meriam 350DN2000 Pressure Meter. To save 5%



on your next Full Service Calibration, click here to fill out the form to accompany your item(s).

Please feel free to contact our Service Department for more info, via email or phone, toll-free at 1-888-223-6763.

BC Biomedical's New Infusion Pump Testers



The BC Biomedical IPA-1000 Infusion Pump Analyzer series is a microprocessor based system that tests flow rates. One or two chamber models available.

- ♦ Easy to use ◆ Easy to clean
- Concurrent operation of 2 chambers
- Graphic LCD display
- ♦ Auto chamber recognition
- ♦ Two chamber sizes (3.5 ml & 35 ml)